

Schedule of Accreditation



Organisation Name	Nelipak Laboratory Services Ltd
Trading As	Nelipak Laboratory Services Ltd.
INAB Reg No	263T
Contact Name	Mark Kelada
Address	Kilbeggan Road, Clara, Offaly, R35 F583
Contact Phone No	057 9331 888
Email	mark.kelada@nelipak.com
Website	https://www.nelipak.com/services/laboratory-services/
Accreditation Standard	EN ISO/IEC 17025 T
Standard Version	2017
Date of award of accreditation	01/06/2010
Scope Classification	Mechanical testing
Services available to the public ¹	

¹ Refer to document on interpreting INAB Scopes of Accreditation

Sites from which accredited services are delivered		
(the detail of the accredited services delivered at each site are on the Scope of Accreditation)		
	Name	Address
1	Head Office	Kilbeggan Road, Clara, Offaly, R35 F583

Scope of Accreditation

Head Office

Mechanical Testing

Category: A

Product categories - Tests	Test detail	Product detail	Range of Measurement	Equipment/Technique	Std. Ref & SOP
1127 Pulpwood, pulp, paper, paperboard and products - .15 Permeability	Determination of Air Permanence and Air Resistance of Packaging Materials		0.226µm to 56.5µm / Pa s	Bendtsen Porosity Tester	ISO 5636-3:2013
1127 Pulpwood, pulp, paper, paperboard and products - .49 Physical tests	Paper and Board - Determination of Grammage				ISO 536:2019
1129 Plastic and related products - .11 Tension tests	Breaking Force and Elongation of Textile Fabrics			Instron Test Frame	ASTM D5035-11 (R2019) Methods 1C & 2C
	Tensile Properties of Thin Plastic Sheeting			Instron Test Frame	ASTM D882-18
1129 Plastic and related products - .23 Ageing and environmental tests	Accelerated Aging and Real Time Aging of Sterile Barrier Systems		20°C to 70°C 15% RH to 90% RH Ambient conditions for Real Time Aging	Environmental Controlled Chamber	ASTM F1980-21
	Conditioning Containers, Packages or Packaging Components for Testing		-40°C to 80°C 0% RH to 90% RH	Environmental Controlled Chamber	ASTM D4332-22 ASTM F2825-18 ISO 2233:2000 ASTM E171/E171M-11 (R2020)

1129 Plastic and related products - .99 Other tests	Determination of Air Permanence and Air Resistance of Packaging Materials	0.226µm to 56.5µm / Pa s	Bendtsen Porosity Tester	ISO 5636-3:2013
	Package Yield of Plastic Film	Measured as m ² / kg Max sample weight of 0.21kgs	Instron/Zwick Test Frame	ASTM D4321-15
	Slow Rate Penetration Resistance of Flexible Barrier Films and Laminates		Instron/Zwick Test Frame	ASTM F1306-21
	Static and Kinetic Co-efficient of Friction of Plastic Film and Sheeting	Max load 2 kN	Instron/Zwick Test Frame	ASTM D1894-14
1146 Packages and containers - .01 Physical tests	Compression Resistance of Shipping Containers, Components and Unit Loads Compression Resistance of Container under a Constant Load	Max load 22.24 kN	Lansmont Compression Table	ASTM D642-20 ASTM D4577-05 (2023)
	Concentrated Impacts to Transport Packages - Guided Fall			ASTM D6344-04 (2017)
	Detection of Gross Leaks in Medical Packaging by Internal Pressurization (Bubble Leak)			ASTM F2096-11 (R2019)
	Detection of Leaks in Nonporous Medical Packaging by Dye Penetration			ASTM F3039-15 Methods A & B
	Detection of Seal Leaks in Porous Medical Packaging by Dye Penetration			ASTM F1929-23 Methods A, B & C
	Determination of the Effects of High Altitude on Packaging Systems by Vacuum Method	100 mbar to 1000 mbar	Heraeus Vacuum Chamber	ASTM D6653/D6653M-13 (R2021)
	Drop Testing of Loaded Containers by Free Fall	Max capacity 79 kg Max drop height 1.8 m Min drop height: 125 mm	Lansmont Drop Tester	ASTM D5276-23
	Fixed Displacement Vibration, Rotary Motion	Max load 45 kg Peak-peak displacement 1" Frequency range 2 to 5Hz	Rotary Vibration Table	ASTM D999-08 (2023) Method A2

	Fixed Displacement Vibration, Vertical Motion	Max load 110 kg	Vertical Vibration Table	ASTM D999-08 (2023) Method A1
	Internal Pressurization Failure Resistance of Unrestricted Packages (Burst Test)	Pressure range 5 psi to 50 psi	Cobham Burst Tester	ASTM F1140/F1140M-13 (R2020)
	Random Vibration of Shipping Containers	Max Load 110kg	Vertical Vibration Table	ASTM D4728-22
	Seal Strength of Flexible Barrier Materials	Up to 2kN	Instron Test Frame	ASTM F88/F88M-23
	Stacked vibration	Max 110kg	Vertical Vibration Table	ASTM D4169-23, Schedule D, Stacked vibration
	Transportation testing	Minimum drop height: 125 mm		ASTM D4169-23, DC2, DC3, DC4, DC5, DC6, DC12, DC13, DC14, DC15, DC17 ISTA 1A ISTA 1C ISTA 1G ISTA 2A ISTA 2B
1146 Packages and containers - .99 Other tests	Visual Inspection			ASTM F1886/1886M-16